

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
2 August 2001 (02.08.2001)

PCT

(10) International Publication Number
WO 01/55052 A1

(51) International Patent Classification⁷: C04B 22/16, 22/12

(74) Agents: MURPHY, Kevin, P. et al.; Swabey Ogilvy Renault, Suite 1600, 1981 McGill College Avenue, Montreal, Quebec H3A 2Y3 (CA).

(21) International Application Number: PCT/CA00/00070

(22) International Filing Date: 26 January 2000 (26.01.2000)

(25) Filing Language: English

(26) Publication Language: English

(81) Designated States (*national*): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(71) Applicant (*for all designated States except US*): DOM-TAR INC. [CA/CA]; 395 de Maisonneuve Boulevard West, Montreal, Quebec H3C 2M1 (CA).

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(72) Inventors; and


(75) Inventors/Applicants (*for US only*): MALRIC, Bernard [FR/FR]; 2281, chemin de l'Etraz, F-01220 Divonne les Bains (FR). LUTZ, Theophil [CH/CH]; 6, avenue Coderey, CH-1110 Morges (CH).

Published:

— with international search report

[Continued on next page]

(54) Title: POTASSIUM MONOFLUOROPHOSPHATE AS A CORROSION INHIBITOR



(57) Abstract: Potassium monofluorophosphate is found to be superior to sodium monofluorophosphate as a corrosion inhibitor for steel reinforcement members in reinforced concrete: conveniently the potassium monofluorophosphate in aqueous solution is



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

POTASSIUM MONOFLUOROPHOSPHATE AS A CORROSION INHIBITOR

TECHNICAL FIELD

This invention relates to a method of inhibiting corrosion of steel
5 reinforcing members in concrete and to a treated reinforced concrete.

BACKGROUND ART

US Patent 5,071,579, issued December 10, 1991, of Domtar Inc.,
describes the use of sodium fluorophosphate, also known as "sodium
monofluorophosphate" and abbreviated as "MFP", to prevent corrosion of
10 reinforced concrete containing steel rebars when such concrete is exposed
to a corrosive environment, for example, chloride ions.

Carbonation of concrete results from penetration of carbon dioxide
from the air into the concrete and reaction of the carbon dioxide with
hydroxides such as calcium hydroxide in the concrete. Carbonation lowers
15 the alkalinity of the concrete. High alkalinity is needed to protect
embedded steel rebars from corrosion.

As described in the US Patent establishment of galvanic corrosion
cells at the steel rebars results in corrosion of the steel, with creation of
expansive forces which destroy the concrete.

20 Concrete is used in the construction of buildings and in the
manufacture of articles including paving slabs, structural members,
curbing, gutters, pipes and other cast articles.

WO 92/14796 published September 3, 1992, Domtar Inc., describes
the use of the aforementioned sodium fluorophosphate to reduce scaling
25 due to freezing and thawing of concrete, particularly when a deicer such as
sodium chloride is used to deice the surface of the concrete.

The present invention seeks to provide improvements in the
inhibition of corrosion of steel reinforcing members in concrete and an

improved treated concrete, employing potassium monofluorophosphate in place of or in combination with sodium monofluorophosphate.

DISCLOSURE OF THE INVENTION

In accordance with one aspect of the invention there is provided a
5 method of inhibiting corrosion in a reinforced concrete containing steel reinforcing members comprising contacting the reinforced concrete with potassium monofluorophosphate.

In accordance with another aspect of the invention there is provided a reinforced concrete containing steel reinforcing members and having a
10 concrete surface, said concrete containing potassium monofluorophosphate.

DESCRIPTION OF PREFERRED EMBODIMENTS

i) Application of Potassium Monofluorophosphate

Suitably an aqueous solution of the potassium monofluorophosphate is contacted with the concrete. In particular, the aqueous solution is
15 contacted with a surface of the reinforced concrete such that the solution containing dissolved potassium monofluorophosphate penetrates into the concrete and deposits the potassium monofluorophosphate in a penetration zone extending inwardly into the concrete, from the concrete surface, and from which the potassium monofluorophosphate migrates to the steel
20 reinforcing members.

By "penetration zone" is to be understood a depth of the concrete, determined from the concrete surface which is contacted with the solution within which the solution of potassium monofluorophosphate penetrates, and which extends towards the steel reinforcing members, for example,
25 steel rebars.

It will be understood that additives for other purposes may be present in the aqueous solution, but the solution should be free of chemicals

that promote corrosion or that would otherwise detract from the objective of inhibiting corrosion.

It will be recognized that the potassium monofluorophosphate could be contacted with the concrete surface in solution in other vehicles for example, organic solvents, without departing from the spirit of the invention. However, from a practicable standpoint an aqueous vehicle is by far preferred.

Conveniently the aqueous solution employed in the invention may contain up to 35%, by weight, and typically 5 to 20%, by weight, of the potassium monofluorophosphate.

The solution may be contacted with the concrete by various methods depending on the form of the concrete article or structure which is to be treated. By way of example, the aqueous solution of potassium monofluorophosphate may be sprayed, painted, brushed or otherwise applied as a coating on an exposed concrete surface. The solution should be applied in an amount to achieve a desired penetration into the concrete to reach the steel rebar reinforcing members.

The concrete may also be soaked in the solution, for which purpose a dike may be built around the concrete to retain the solution during a soaking period.

The invention is not restricted to application by means of a solution of the potassium monofluorophosphate and the latter may be applied in a powder form to the concrete surface, or in a gel.

The potassium monofluorophosphate should penetrate the reinforced concrete to reach the steel rebars which are the reinforcing members in the concrete. Typically the rebars are disposed at up to 35 mm from the concrete surfaces in buildings, and at up to 60 mm in highway structures. At these locations corrosion of the rebars is a problem.

It is especially advantageous to apply the potassium monofluorophosphate when the reinforced concrete is in a substantially dry state, in which state the capillary passages in the concrete are open for migration of the potassium monofluorophosphate into the concrete.

5 **ii) Corrosion Inhibition**

It has surprisingly been found that not only is potassium monofluorophosphate a corrosion inhibitor for reinforced concrete, but also that it is markedly superior to sodium fluorophosphate in providing such corrosion inhibition.

10 It was not previously known and was not predictable that potassium monofluorophosphate would function as a corrosion inhibitor for reinforced concrete, and still less was it predictable that it would be superior to the known corrosion inhibitor sodium fluorophosphate.

15 In order to function as an effective corrosion inhibitor a chemical needs to be an efficient corrosion inhibitor in both alkaline and neutral environments, corresponding to non-carbonated reinforced concretes polluted by chlorides, as well as carbonated reinforced concretes.

20 The chemical needs to be sufficiently stable and for most forms of application, sufficiently soluble in a suitable vehicle, for example, water, to obtain a concentration of the chemical effective for introduction of an effective corrosion inhibiting amount of the chemical into the concrete.

25 The chemical needs migration or penetrating characteristics such that a useful and adequate penetration of the chemical into the reinforced concrete can be achieved; and, in particular, should be capable of migrating along a network of concrete pores and capillaries to reach the steel rebar reinforcing members of the concrete, which are subject to corrosion.

Most desirably a chemical, in order to function as an effective corrosion inhibitor should provide corrosion inhibition to the steel rebars, in low concentrations of the chemical.

While sodium fluorophosphate has previously been identified as an effective corrosion inhibitor for the steel reinforcing members of reinforced concrete other fluorophosphates do not provide such corrosion inhibition; by way of example, lithium monofluorophosphate, ammonium monofluorophosphate, calcium fluorophosphate and strontium fluorophosphate have been evaluated and do not function as corrosion inhibitors for the steel reinforcement members in reinforced concrete. Even when the monofluorophosphate such as ammonium monofluorophosphate have a necessary solubility in water to permit their application to concrete, it is found that an effective penetration or migration of the monofluorophosphate into the concrete does not occur.

The solubility of the fluorophosphate varies over a wide spectrum, additionally while the fluorophosphate anion plays a role in corrosion inhibition it appears that the accompanying cation also has a significant role both with respect to the corrosion inhibiting capacity of the compound and the ability of the fluorophosphate compound to migrate or diffuse into the concrete, through a network of pores and capillaries.

In the present invention it has been found not only that potassium monofluorophosphate functions as an effective corrosion inhibitor for the steel reinforcing members of reinforced, whereas the related lithium, ammonium, tris, calcium and strontium monofluorophosphate do not; but also that potassium monofluorophosphate is markedly superior to sodium monofluorophosphate as a corrosion inhibitor.

In particular potassium monofluorophosphate is found to be up to five times more effective than sodium monofluorophosphate. Typically

potassium monofluorophosphate provides the same level of corrosion inhibition as sodium monofluorophosphate when employed in an amount of one-fifth the amount of sodium monofluorophosphate.

BRIEF DESCRIPTION OF DRAWINGS

5 The invention and the improved corrosion inhibiting effects provided by potassium monofluorophosphate are illustrated by reference to the accompanying drawings in which:

Figure 1 is a photograph illustrating the corrosion inhibiting effects of potassium monofluorophosphate;

10 **Figure 2** is a photograph illustrating, for comparison purposes, the corrosion inhibiting effects of sodium monofluorophosphate employed in the same condition as for potassium monofluorophosphate in Figure 1; and

Figure 3 illustrates the penetration of different
15 monofluorophosphates in concrete.

EXAMPLES

Example 1: Action in Alkaline Environment

 Solutions were prepared with addition of sodium hydroxide to either distilled water or tap water (containing calcium), in order to obtain a pH of
20 about 13, simulating the environment of an uncarbonated concrete. 0.5M of sodium chloride was added to simulate the corrosive environment of concrete contaminated by deicing salts. 2ml portions of the solutions were used in standard plastic tissue culture test plates with 24 positions. Various amounts of potassium monofluorophosphate and sodium monofluoro-
25 phosphate were added to each cell and a nail was immersed in the different solutions and visually observed for the development of pitting corrosion, which usually happens in such a case, during 30 days. Nails were cleaned

in ethyl alcohol with 1% nitric acid added, then rinsed five times in distilled water and transferred directly from distilled water to test solution.

After cleaning the nails and observing them under a magnifying glass, it appears that sodium chloride in that environment yields the formation of corrosion pits, without the development of a general rust on the nail surface. Potassium monofluorophosphate offers a better protection than sodium monofluorophosphate at the 0.1M concentration: no pits were visible whereas with sodium monofluorophosphate, slight pitting could be observed. At 0.5M, there was no corrosion for either inhibitor.

10 **Example 2: Action in Neutral Environment**

This is intended to simulate the chemical environment of carbonated concrete. Tap water was used, because it contains calcium ions which are also present in concrete and play an active role in the corrosion process.

In some of the solutions, 0.5M NaCl was added to simulate carbonated concrete polluted by deicing salts.

Various quantities of sodium monofluorophosphate and potassium monofluorophosphate were also added. The development of the corrosion of nails immersed for thirty days in these solutions was visually observed. The preparation of the solutions and nails is similar to Example 1.

The photographs of Figures 1 and 2 show that a general type of corrosion typical of neutral environments starts developing after only a few hours. The effect of chlorides is in this case secondary. Inhibitors are efficient at a lower concentration than in alkaline media. Potassium monofluoro-phosphate is clearly more efficient as a corrosion inhibitor than sodium monofluorophosphate: it offers at a concentration of 0.01M about the same protection as is provided by sodium monofluorophosphate at a concentration of 0.05M. In other words potassium monofluorophosphate is

five times more effective as a corrosion inhibitor, than sodium monofluorophosphate.

In the photographs of Figures 1 and 2, the corrosion results in a darkening of the nails. The pale coloured nails are the result of effective corrosion inhibition.

Example 3: Concrete Penetration Tests

Concrete slabs having the dimensions 15 x 15 x 2 cm were immersed at one end during 12 hours respectively into 20% aqueous solutions of:

- 10 sodium monofluorophosphate
- potassium monofluorophosphate
- ammonium monofluorophosphate
- Tris monofluorophosphate.

Tests with the known inhibitor sodium monofluorophosphate were redone a second time to ensure representativity.

Concentration profiles of the monofluorophosphates were measured using ion chromatography to accurately quantify fluorophosphate ions only in that they constitute an active inhibitor part.

Results show that only sodium and potassium monofluorophosphates were able to penetrate significantly into concrete, performance of both products being similar. There is no significant difference between the penetrating performance of the two products.

It was, however, notable and perhaps unexpected that ammonium and tris monofluorophosphates did not penetrate the concrete as both of these products have a high solubility in water. It thus appears that the performance of monofluorophosphates into concrete may depend in a large measure on the cation present.


CLAIMS

1. A method of inhibiting corrosion in a reinforced concrete containing steel reinforcing members comprising:
contacting the reinforced concrete with potassium monofluoro-
5 phosphate.
2. A method according to claim 1, wherein said potassium monofluorophosphate is in an aqueous solution.
- 10 3. A method according to claim 2, which comprises contacting a surface of said reinforced concrete with said aqueous solution such that potassium monofluorophosphate in said solution penetrates into said reinforced concrete.
- 15 4. A method according to claim 2 or 3, wherein said solution contains up to 35%, by weight, potassium monofluorophosphate.
5. A method according to claim 4, wherein said solution contains from 5 to 20%, by weight, potassium monofluorophosphate.
20
6. A reinforced concrete containing steel reinforcing members and having a concrete surface, said concrete containing potassium monofluorophosphate.
- 25 7. A reinforced concrete according to claim 6, wherein said potassium monofluorophosphate is present in a zone of the concrete extending inwardly of said concrete.

1/3

POTASSIUM MONOFLUOROPHOSPHATE


Inhibitor concentration

Fig. 1

2 / 3

SODIUM MONOFLUOROPHOSPHATE

Inhibitor concentration



F3E-2

3/3

Penetration of fluorophosphates into concrete




FIG. 3

INTERNATIONAL SEARCH REPORT

International Application No

PCT/CA 00/00070

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 C04B22/16 C04B22/12

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C04B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, CHEM ABS Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 071 579 A (MASON DEAN ET AL) 10 December 1991 (1991-12-10) cited in the application column 2, line 44 - line 61 claims 1-3; example 24 ---	1-7
A	US 4 613 450 A (MORAN FRANCIS ET AL) 23 September 1986 (1986-09-23) examples 2,9; table I claims 1,3 ---	1,2
A	WO 92 14796 A (DOMTAR INC) 3 September 1992 (1992-09-03) cited in the application claims 1,2 ---	1,2
	--- -/--	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"8" document member of the same patent family

Date of the actual completion of the international search

15 September 2000

Date of mailing of the international search report

22/09/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-2016

Authorized officer

Puettz C.

INTERNATIONAL SEARCH REPORT

Inte: nal Application No

PCT/CA 00/00070

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>US 4 153 478 A (PARANT BERNARD ET AL) 8 May 1979 (1979-05-08) claims 1,13; example 4 -----</p>	1,2

INTERNATIONAL SEARCH REPORT

Inter national Application No

PCT/CA 00/00070

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5071579	A	10-12-1991	AT 121465 T	15-05-1995
			CA 1339004 A	25-03-1997
			DE 3853624 D	24-05-1995
			DE 3853624 T	12-10-1995
			EP 0322183 A	28-06-1989
			ES 2074052 T	01-09-1995
			FI 885862 A,B,	18-06-1989
			HK 32596 A	01-03-1996
			NO 303457 B	13-07-1998
			US 5127954 A	07-07-1992
US 4613450	A	23-09-1986	JP 2153876 A	13-06-1990
			JP 2880516 B	12-04-1999
			FR 2527643 A	02-12-1983
			AT 25113 T	15-02-1987
			AU 559671 B	19-03-1987
			AU 1485683 A	01-12-1983
			AU 7454687 A	08-10-1987
			CA 1202169 A	25-03-1986
			DE 3369349 D	26-02-1987
			EP 0096619 A	21-12-1983
WO 9214796	A	03-09-1992	JP 1643084 C	28-02-1992
			JP 3002234 B	14-01-1991
			JP 58213884 A	12-12-1983
			ZA 8303824 A	29-02-1984
			AT 130025 T	15-11-1995
			AU 656172 B	27-01-1995
			AU 1237092 A	15-09-1992
			BG 98035 A	27-05-1994
			BR 9205636 A	02-08-1994
			CA 2104026 C	23-09-1997
US 4153478	A	08-05-1979	CZ 9301651 A	13-04-1994
			DE 69205968 D	14-12-1995
			DE 69205968 T	25-04-1996
			DK 571456 T	18-03-1996
			EP 0571456 A	01-12-1993
			ES 2079854 T	16-01-1996
			FI 933591 A	13-08-1993
			GR 3018942 T	31-05-1996
			HU 66991 A	30-01-1995
			JP 6508335 T	22-09-1994
US 4153478	A	08-05-1979	NO 301025 B	01-09-1997
			SK 87393 A	12-01-1994
			US 5314755 A	24-05-1994
			FR 2352895 A	23-12-1977
			AU 504865 B	01-11-1979
			AU 2436077 A	26-10-1978
			BE 852452 A	01-07-1977
			CA 1080093 A	24-06-1980
			CH 601489 A	14-07-1978
			DE 2717541 A	03-11-1977
US 4153478	A	08-05-1979	FR 2530649 A	27-01-1984
			GB 1559255 A	16-01-1980
			JP 52129640 A	31-10-1977
			PT 66315 A,B	01-04-1977
			US 5127954 A	07-07-1992
			JP 2153876 A	13-06-1990
			JP 2880516 B	12-04-1999
			FR 2527643 A	02-12-1983
			AT 25113 T	15-02-1987
			AU 559671 B	19-03-1987